

Name _____

Date Due _____

READ ALL DIRECTIONS BEFORE BEGINNING

TODDLER PANTS – Cutting Layout



Complete CMI sample prior to starting this project.

1. Check pattern pieces to make sure you have both a front & a back of the same size. If your pattern has not been previously cut, choose size and cut out pattern pieces.
2. Fold pre-washed fabric according to **Cutting Layout** below. Lay pattern pieces on fabric with grainline arrows parallel to the selvage. Pin.

SELVAGES

SELVAGES

Illustration

Illustration

FOLD

FOLD

**One-way
Design**

**Two-way
Design**

3. Put your name & sewing machine # on the whiteboard when you are ready for the teacher to check your cutting layout. DO NOT CUT.

❖ OK to Cut _____ (teacher signature)

4. When OKed use assigned bent handled shears, stand while cutting, cut notches out away from the seam allowance.
5. DO NOT throw fabric scraps away. Place large pieces in designated box.
6. DO NOT throw pattern pieces away, put back in zip lock bag and store in your tote basket till the project is completed.

 Complete Overedge Seam sample prior to starting sewing directions.

COMMUNITY SERVICE TODDLER PANTS

Sewing Directions:

READ ALL DIRECTIONS!

View examples on wall in classroom before beginning each step.



OUTSIDE LEG

Pin at right angles, FRONT to BACK, right sides together at outside leg seam, matching notches.

Illustrations

STOP – Required Quality Check

Show teacher your Toddler Pants.

Teacher will initial if you can proceed. _____

Teacher checks cutting. _____

Stitch side seams evenly 5/8". Secure seams by backstitching.

Trim neatly 1/4" of seam allowance.

Zigzag seam allowance to reinforce and finish.

Press seam flat.



INSIDE LEG

Pin FRONT to BACK right side together at inside leg seam, match notches.

Stitch side seams evenly 5/8". Secure seams by backstitching.

Trim neatly 1/4" of seam allowance

Zigzag seam allowance to reinforce and finish.

Press seam flat.



CROTCH

With RIGHT sides together, insert one leg inside the other.

Pin matching inside leg seams.

Fold seam opposite directions to reduce bulk.

Stitch side seams evenly 5/8". Secure seams by backstitching.

Trim neatly 1/4" of seam allowance

Zigzag seam allowance to reinforce and finish.

Press front and back seam flat.



Complete Casing sample prior to this step.



CASING

Using a **measuring gauge** measure and turn raw edge 1/4" to inside.

Using a **measuring gauge** measure and turn folded edge 1-1/8" to inside.

Pin at right angles. Press casing.

❖ **STOP** – Required Quality Check

Show teacher your Toddler Pants.

Teacher will initial if you can proceed. _____

Stitch close to lower folded edge of casing, leave a 1" opening at center back seam to insert elastic.



LABEL (tag)

Pin over center back seam, just below casing.

Stitch neatly around label pivoting at corners.

Backstitch to secure stitching.



ELASTIC

Using a **safety pin**, insert elastic through casing.

Overlap ends and hold with the safety pin.

Check to make sure elastic is not twisted.

Stitch end of elastic together securely.

Stitch opening neatly closed at center back seam.



HEM

Using a **measuring gauge** measure raw edge 1/2" and turn to inside TWICE.

REPEAT for other leg!

Pin at right angles. Press hem.

❖ **STOP** – Required Quality Check

Show teacher your Toddler Pants.

Teacher will initial if you can proceed. _____

Stitch evenly close to folded edge.

Backstitch to secure.



PRESENTATION

Clip threads. Press. Fold. (See Ms. Vetter if you need help repairing any holes, tucks, etc.)

Name _____ Period _____

TODDLER PANTS EVALUATION

♦♦ Student grades self on a scale of 1-4, 4 being the best.

- Cutting _____ Referred to Cutting Layout. Grainlines parallel to selvage. Neatly cut with notches cut out away from pattern. ♦♦ *Teacher OKed*
- Pinning _____ Right sides together, raw edges even, pin at right angles, one front and one back together at side seams. ♦♦ *Teacher OKed*
- Outside
Leg
Seams _____ Machine correctly threaded for even tension. Seam allowance, even & straight, 5/8" (1.5cm). Seam allowance neatly trimmed to 1/4". Seams secured with backstitching. Zigzag finish neatly centered over cut edge. Seam pressed to one side.
- Inside
Leg
Seams _____ Same as #3.
- Crotch _____ Same as #3 & #4. Seams match.
- Casing _____ Raw edge turned to wrong side 1/4". Casing even 1-1/8", stitched evenly close to folded edge leaving a 1-1/8" opening at center back seam, press. ♦♦ *Teacher OKed*
- Tag _____ Placed below and parallel to casing at center back seam. Neatly & securely stitched close to edge of tag around all sides pivoting at corners.
- Elastic _____ Not twisted, securely sewn, 1" opening neatly stitched at center back seam close to folded edge, w/o stitching elastic.
- Hem _____ Raw edge turned under twice and even 1/2". Neatly stitched close to fold, pressed. ♦♦ *Teacher OKed*
- Overall _____ Overall neatness: clean, pressed, threads clipped, no holes, etc. Work Habits, Read & Followed Directions, stayed On Task.

=====
40

Total Points Possible

♦♦ **Inside zip lock bag: put completed pants, pattern pieces, spool of thread & completed evaluation with your name & class period. TURN IN!**